



# TexSpray™ GTX™ 2000EX

Professional Pumping System for Texture Spraying



PROVEN QUALITY. LEADING TECHNOLOGY.



# TexSpray GTX 2000EX



**FAST!**

The GTX 2000EX is the perfect pumping system for the professional texture contractor who has access to a high-output air compressor. With its unmatched performance and durability, it can easily apply common interior drywall mud finishes such as orange peel, splatter and knockdown, or the more demanding deck coatings and exterior aggregate acrylic and elastomeric finishes.

## Versatile Pump-Only Texture Sprayer

- ▶ Field proven durability and performance
- ▶ Allows your compressor to be placed outside while completing interior projects
- ▶ Designed for use with a user-supplied air compressor\*

## On-Board Air Filtration System

- ▶ Filters incoming air to keep your sprayer running at optimal performance
- ▶ Auto-drain design automatically removes moisture build-up



## Husky™ 1040 Double Diaphragm Pump

- ▶ High-output, 1-in (25 cm) pump produces texture delivery rates to 4.0 gpm\*
- ▶ Durable Geolast™ Ball Check Valves

## Separate Pump and Gun Air Controls

- ▶ One regulator controls pump pressure and output, another controls atomization air
- ▶ Enables you to produce precise, consistent and repeatable texture finishes



## Heavy-Duty Air Spray Trigger Gun

- ▶ Durable cast aluminum design
- ▶ Oversized fluid passages for pumping heavy mud mixes
- ▶ Extra-course gun head threads for quick nozzle changes

## Largest Capacity Hopper

- ▶ 17-gallon capacity
- ▶ Steep sides to keep the thickest muds flowing to the pump
- ▶ No-tools removal for easy cleanup

## Bonded Material/Air Hose

- ▶ Both hoses are permanently bonded together for easy handling
- ▶ No-tools hose connection with oversized grip



**PART NO:** 257030  
**MAX GPM:** 4.0 (15.1 LPM)\*  
**MAX PSI:** 120 (8.3 BAR)  
**MAX HOSE†:** 100 ft (30 m)

### Comes complete with:

- ▶ 1 in x 25 ft (25.4 mm x 7.5 m) Hose
- ▶ Air Spray Trigger Gun
- ▶ 6 Nozzles

See Graco's Texture Sprayer brochure for the complete line of professional texture sprayers and accessories.

\*Air compressor with minimum performance of 12 CFM at 100 psi (340 LPM at 6.9 BAR) recommended.

†Hose length is dependent on material viscosity.

Call today for product information or to request a demonstration.

**877.84GRACO** (1-877-844-7226) or visit us at [www.graco.com](http://www.graco.com).

