

Airless Spray Equipment

TACKLE ANY JOB WITH CONFIDENCE!







Featuring a full line of Airless Paint Sprayers, Heavy-Duty Pressure Washers, Texture Sprayers, and Accessories.

Table of Contents

| Page 1 | .Why Airless Spray - Selection Chart |
|---------|--|
| Page 2 | .Zip Spray [™] ESP, 1700, 2100 Plus |
| Page 3 | .Zip Spray 2300 Plus, 2700 Plus, 3100 Plus |
| Page 4 | .Zip Spray 3600 G Plus & Accessories |
| Page 5 | .Airless Accessories - Guns |
| Page 6 | .Airless Accessories - Pressure Rollers, Mini Poles |
| Page 7 | .Airless Accessories - Maxi Poles, Gun Filters, Repair Kits, AngleHead™ & Fittings |
| Page 8 | .Tip Selection Guide Reversible Tip |
| Page 9 | .Tip Selection Guide Standard Reversible Uni-Tip™, Striping & Fine Finish |
| Page 10 | .Super Zip™ Tip Selection Guide |
| Page 11 | .Flat Tip Selection Guide |
| Page 12 | .Texture Application Guide |
| Page 13 | .Texture Intro - Zip-Tex™ 650 |
| | .Texture Zip-Tex 900, ASM Professional Contractor Hopper Gun |
| Page 15 | .Texture Hopper, Accessories & Replacement Parts |
| Page 16 | .Pressure Washers - Zip Clean [™] 2525 |
| Page 17 | .Pressure Washers - Zip Clean 2730, 3030 & Accessories |
| Page 18 | .Fluids |
| Page 19 | .Merchandising Displays |
| Page 20 | .Electric Airless Product Specifications & Comparison Guide |
| Page 21 | .Gas Engine Airless Product Specifications, Zip-Tex Units, |
| | Prossura Washers & Comparison Guida |



ASM MAKES PROJECTS A ZIP!

For use with a variety of coatings including stains, enamels, interior/exterior latex and oil-based paints.

EASIER! Professional results made easy!

Uniform and professional results are now a zip! ASM's Zip-Spray Airless Sprayers & Texture Units produce a high-quality finish on every job they tackle!

FASTER! Finish large projects fast!

ASM's Zip-Spray Airless Sprayers are up to 10X faster than brushing and 4 times faster than traditional rolling. Save time and increase your productivity.

AFFORDABLE! Save Money!

ASM's Zip-Spray Airless Sprayers & Texture Units pay for themselves in just over one project.

- Enjoy increased productivity and finish the job fast
- Contractors save money by reducing both on-the-job time and down time
- Save money on paint with professional coverage and a smooth finish every time

Why Airless Spray?

Airless spray is 10 times faster than brushing, and 4 times faster than traditional rolling. Airless spray provides even material coverage on all types of surfaces. You can spray most common coatings, including stains, latex, and oil-based paints. And best of all, airless spray saves you money!

Zip-Spray airless spray systems are designed to save time by increasing your productivity and reducing downtime. They are durable, perfect for rugged job site conditions. They are easy to operate and transport for convenience as you work. And you'll find that Zip-Spray airless sprayers still offer the innovation and value you've come to expect from ASM.

Airless Equipment Selection Chart

| | Highest Operating Pressure | Delivery Rating | Max Tip Size Supported | Recommended Annual Use | Typical Coatings | Ideal Users |
|--------------------|--|--------------------|---------------------------|--|---|----------------|
| Zip-Spray ESP | 2800 psi (19.3 MPa, 193 bar) | .24 gpm (.91 lpm) | .015 in (.381 mm) | Roll: 1000 gal (3785 L) Spray: 175 gal (662 L) | Varnish, Enamels, Primers, Interior/Exterior Latex | Light-Duty |
| Zip-Spray 1700 | 3000 psi (20.7 MPa, 207 bar) | .31 gpm (1.17 lpm) | .017 in (.432 mm) | Roll: 1500 gal (5678 L) Spray: 300 gal (1135 L) | Varnish, Enamels, Primers, Interior/Exterior Latex | Medium-Duty |
| Zip-Spray 2100 PL | US 3300 psi (20.7 MPa, 207 bar) | .47 gpm (1.8 lpm) | .021 in (.483 mm) | 1000 gal (3785 L) | Varnish, Enamels, Primers, Interior/Exterior Latex | Heavy-Duty |
| Zip-Spray 2300 PL | US 3300 psi (22.7 MPa, 227 bar) | .54 gpm (2.0 lpm) | .023 in (.584 mm) | 1250 gal (4732 L) | Varnish, Enamels, Primers, Interior/Exterior Latex & Heavier Bodied Latex | Heavy-Duty |
| Zip-Spray 2700 PL | US 3300 psi (22.7 MPa, 227 bar) | .86 gpm (3.25 lpm) | .027 in (.686 mm) | 1500 gal (5678 L) | Varnish, Enamels, Primers, Interior/Exterior Latex & Heavier Bodied Latex | Pro-Duty |
| Zip-Spray 3100 PL | US 3300 psi (22.7 MPa, 227 bar) | 1.1 gpm (4.2 lpm) | .031 in (.787 mm) | 1500 gal (5678 L) | Varnish, Enamels, Primers, Interior/Exterior Latex & Heavier Bodied Latex | Pro-Duty |
| Zip-Spray 3600 G I | PLUS 3300 psi (22.7 MPa, 227 bar) | 1.25 gpm (4.7 lpm) | .036 in (.912 mm) | 1500 gal (5678 L) | Block Fillers & Elastomerics, Enamels, Primers, Interior/Exterior Latex & Heavier Bodied Latex | Pro-Duty |

Zip-Spray ESP

Light-Duty Electric Airless Sprayer

The Zip-Spray ESP offers convenience, durability, and value for tradesmen with occasional painting needs, homeowners, and do-it-yourselfers. Ideal for use with paint spraying and paint pressure rolling applications (pressure roller kit sold separately).

Zip-Flush™ Cleaning

• Connect to a garden hose and clean the pump, hoses, and gun in minutes!

Lightweight Design

- Portable and easy to store. Weighs only 13 lbs (5.9 kg)
- 4-legged stand is durable and stable

Demand Delivery System

- Pump runs only when gun trigger is activated, reducing sprayer wear
- Draws from a 1 or 5 gallon container

Simple Piston Design

- For reliable performance and long life
- Max tip supported .015

Includes:

- ASM 200 Contractor Spray Gun with 4-Finger Trigger
- 515 Uni-Tip with Uni-Tip Hand-Tight[™] Base
- 1/4 in x 25 ft (6.4 mm x 7.5 m), 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life™ Protectant Fluid





Part# 248772 UPC# 769946084481

Zip-Spray 1700

Medium-Duty Electric Airless Sprayer

The Zip-Spray 1700 is ideal for moderate spraying needs, including property maintenance, remodeling, and light commercial projects.

Zip-Flush Cleaning

- Connect to a garden hose and clean the pump, hoses, and gun in minutes!
- Pump lower is modular design for easy repair and maintenance

Easy to transport and store

- Rugged cart with fold-down handle and 75 ft (23 m) capacity hose rack is maneuverable and convenient to store
- Pail hook holds paint bucket for easy transport on job site and reduces spilling

Durable Piston Pump

- Stainless steel pump resists corrosion for long life
- Modular piston is removable for easy quick repair and replacement
- Max tip supported .017

Includes:

- 500 Series Contractor Spray Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight Base
- 1/4 in x 50 ft (6.4 mm x 15 m), 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life Protectant Fluid



Modular Displacement Pump Part# 245569

Part# 233789 UPC# 769946075632

Zip-Spray 2100 Plus

Heavy-Duty Electric Airless Sprayer

The Zip-Spray 2100 Plus is great for contractors, property owners, handymen, and remodelers with frequent spraying needs.

Industry-Proven Hardened Chrome and Stainless Steel Piston Pump *Outlasts competitive pumps by 65%*.

Durable Piston Pump

- Double-Acting pumps paint on both the up and the down stroke for consistent delivery
- Long-Lasting Packings Ultra high molecular weight polyethylene (UHMWPE) construction
- Wiper Ring Packing Wipes the inside of the pump clean, extending life up to 50%
- Rotating Ball Checks Maximize component life by eliminating wear on a single surface
- Trouble free electro-mechanical pressure control for smooth spraying.
- Max tip supported .021

- Pump lower knocks off using only a hammer for easy repair and maintenance
- Reliable DC motor
- Long extension cords can be used

Includes:

- 500 Series Contractor Spray Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight Base
- 1/4 in x 50 ft (6.4 mm x 15 m), 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life Protectant Fluid, Packing Seal™



Part# 247482 UPC# 769946090048

Part# 247485 UPC# 769946090055

Zip-Spray 2300 Plus

Heavy-Duty Electric Airless Sprayer

The Zip-Spray 2300 Plus is perfect for professionals who spray 3-5 times a week for most painting applications.

Heavy-Duty Piston Pump

- Pump lower knocks off easily for convenient maintenance and repair
- Max tip supported .023

Electronic Pressure Control

• Trouble free electro-mechanical variable speed pressure control for smooth spraying.

Fan-Cooled DC Motor

• Run longer extension cord

Full-Flow Manifold Filter

- Filter screen comes out with the cap for less mess
- Full-flow design flushes completely and cleans up quickly
- · Reduces tip clogs and improves finish

Welded Steel-Chrome Plated Cart

Features a retractable handle

Includes

- 500 Series Contractor Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight base
- 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life Protectant Fluid, Packing Seal



Zip-Spray 2700 Plus

Pro-Duty Electric Airless Sprayer

The Zip-Spray 2700 Plus is designed for professional contractors in many applications, from residential to commercial. Supports 2 guns.

Heavy-Duty Piston Pump

- Pump lower knocks off easily for convenient maintenance and repair
- Max tip supported .027

Electronic Pressure Control

• Maintains consistent fan pattern for a better finish

Enclosed Design, Fan-Cooled Brushless DC Motor

- Major components are protected from dirt, dust, and overspray
- Run longer extension cord

Full-Flow Manifold Filter

- Filter screen comes out with the cap for less mess
- Full-flow design flushes completely and cleans up quickly
- Reduces tip clogs and improves finish

Welded Steel-Chrome Plated Cart

• Features a retractable handle

Includes

- 500 Series Contractor Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight base
- 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life Protectant Fluid, Packing Seal



Zip-Spray 3100 Plus

Pro-Duty Electric Airless Sprayer

The Zip-Spray 3100 Plus is designed for professional contractors in many applications, from residential to commercial including some block filler and elastomerics. Supports 2 guns.

Heavy-Duty Piston Pump

- Pump lower knocks off easily for convenient maintenance and repair
- Max tip supported .031

Electronic Pressure Control

• Maintains consistent fan pattern for a better finish

Enclosed Design, Fan-Cooled Brushless DC Motor

- Major components are protected from dirt, dust, and overspray
- Run longer extension cord

Full-Flow Manifold Filter

- Filter screen comes out with the cap for less mess
- Full-flow design flushes completely and cleans up quickly
- Reduces tip clogs and improves finish

Welded Steel-Chrome Plated Cart

Features a retractable handle

Includes

- 500 Series Contractor Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight base
- 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (22.7 Mpa, 227 bar) airless paint hose
- Pump Life Protectant Fluid, Packing Seal



Zip-Spray 3600 G Plus

Pro-Duty Gas Mechanical Airless Sprayer Complete

The Zip-Spray 3600 G Plus is perfect for professional painting contractors who demand high output and portability where electricity is unavailable or inconvenient. Sprays architectural coatings, light block fillers and light elastomerics. Supports up to 3 guns.

Full Flow Filter

- Cleans from the inside out
- Reduces tip clogs

Electronic Pressure Control

- Provides excellent spray pattern
- Superior spray finish

Honda power

- Highly reliable
- Portable Power

Drive System

- Heavy-duty clutch Adjusts and aligns itself for long life
- Hardened gears Durable and guiet operation

Heavy-Duty Chrome Over Steel Frame

• Rust resistant for long life

Heavy-Duty Pump

- Knocks off easily for convenient maintenance
- Long wearing rod
- Max tip supported .036

Drain Tube

Safe, durable and built to last

Lift Handles

• One person loading and unloading

Includes

- 500 Series Contractor Gun with 2-Finger Trigger
- 517 Uni-Tip with Uni-Tip Hand-Tight base
- 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (22.7 MPa, 227 bar) airless paint hose
- Pump Life Protectant Fluid, Packing Seal



ACCESSORIES

Airless Hose

- 3300 psi (22.7 MPa, 227 bar) rating
- Swivel couplers and spring guards on both ends
- Can be coupled with other airless hose
- Female fitting ends.

Part # HSE1450 1/4 in (6.4 mm) x 50 ft (15 m)
Part # HSE3850 3/8 in (9.5 mm) x 50 ft (15 m)
Part # 245449 1/4 in (6.4 mm) x 25 ft (7.5 m)

Whip Hose

• Whip Hoses add flexibility and reduce operator fatigue

Part # HSE3163 3 ft (0.9 m) x 3/16 in (4.8 mm) (MXF) Part # HSE3165 5 ft (1.5 m) x 3/16 in (4.8 mm) (MXF)

Gun Hose Kits

• 500 Series Contractor Gun with Uni-Tip, Hand-Tight Base, and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose ("G" thread only)

Part # 256244 (4-Finger) Part # 256245 (2-Finger)

• 400 Series Professional Gun with Uni-Tip, Uni-Tip Hand-Tight Base, and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose

Part # 248249 ("G" thread only) (4-Finger)

Part # 248250 ("G" thread only) (2-Finger)

• 400 Series Professional Gun with Super-Zip, Hand-Tight Base and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose

Part # 451-SHF ("F" thread), 451-SHG ("G" thread) (4-Finger)
Part # 456-SHF ("F" thread), 456-SHG ("G" thread) (2-Finger)

• 300 Series Contractor Gun with Super-Zip, Hand-Tight Base, and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose

Part # 351-SHF ("F" thread), Part # 351-SHG ("G" thread) (4-Finger)
Part # 356-SHF ("F" thread), Part # 356-SHG ("G" thread) (2-Finger)







Gun & Hose Connectors

Part # 4410 3/8 in (npt) x 3/8 in (npt) MBE

Part # 4413 1/4 in (npt) x 1/4 in (npt) Hex Nipple MBE

Part # 4414 1/4 in (npt) x 3/8 in (npt) MBE

Part # 162485 3/8 in (npt) x 3/8 in (npsm) MBE

Part # 239663 1/4 in (npt)(M) x 1/4 in (npsm)(F) Swivel

THREAD SIZE ON DIFFUSER "F" = 11/16 "G" = 7/8

500 Series Professional Airless Spray Gun

The ASM 500 Contractor Gun is new and designed for durability, spraying performance and a long life

- Lightweight gun with easy trigger pull
- Includes 517 Uni-Tip & Guard
- Heavy-duty swivel allows easy gun movement
- Split handle for easy filter removal
- Available "G" thread only
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
 Part # 289316 2-Finger Gun with Uni-Tip
 Part # 288681 4-Finger Gun with Uni-Tip

Repair Kit # 288817





400 Series Professional Airless Spray Gun

- Improved! Life of the 400 Series gun before repair is equal to or better than that of competitive guns
- Heavy-duty swivel allows easy gun movement
- Anodized body resists corrosion
- Split handle for easy access to filter
- Includes 517 Uni-Tip & Guard
- Available with "F" and "G" diffusers to match all systems
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)

Part # 248240 2-Finger Gun with Uni-Tip ("G" thread only)

Part # 456-SF, 456-SG 2-Finger Gun with Super-Zip

Part # 248239 4-Finger Gun with Uni-Tip ("G" thread only)

Part # 451-SF, 451-SG 4-Finger Gun with Super-Zip

Repair Kit # 4427-F, 4427-G





300 Series Professional Airless Spray Gun

- Improved! New needle design for reduced spitting and long life
- Includes 517 Uni-Tip
- Available with "F" and "G" diffusers to match all systems
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)

Part # 248238 2-Finger Gun with Uni-Tip ("G" thread only)

Part # 356-SF, 356-SG 2-Finger Gun with Super-Zip Tip

Part # 248237 4-Finger Gun with Uni-Tip ("G" thread only)

Part # 351-SF, 351-SG 4-Finger Gun with Super-Zip Tip

Repair Kit # 3027-F, 3027-G



200 Series Airless Spray Gun

- Easy-access in-handle paint filter reduces tip clogging and improves finish
- Comfortable 4-Finger Trigger
- Ideal for small projects
- Includes 515 Uni-Tip & Guard
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
 Part # 251-U
 Part # 251-SG
 4-Finger Gun with Uni-Tip
 4-Finger Gun with Super-Zip Tip

Not repairable

Combo Gun

- Well-balanced, lightweight, comfortable handle and trigger
- In-handle gun filter and internal trigger lock
- Add a Mini Pole or Maxi Pole for extra reach

Part # 248241 with 517 Uni-Tip and Uni-Tip Hand-Tight Base ("G" thread only)

Part # 6700-SF, 6700-SG with 517 Super-Zip and Super-Zip Hand-Tight Base

Repair Kit # 6727-F, 6727-G





Zip-Roll™ Pressure Roller

The Zip-Roll pressure roller accessory attaches and is fed paint from your airless pump allowing you to use your system to roll in areas where spraying is not practical. Provides smooth, continuous delivery of paint to all types of surfaces. Just trigger gun to release paint to roller. Pressure rolling is 4 times faster than standard rolling!

- Extends reach no need for a ladder
- Chrome-plated stainless steel frame provides rust resistance and eliminates streaking
- Hand-Tight system for easy assembly no tools required
- Convenient Zip-Clip™ holds roller cover securely on frame and quickly releases for easy cleanup
- Few parts for quicker cleaning time


Zip-Roll Pressure Roller

| (Includes Combo Gun) | 3 ft | 6 ft |
|---------------------------------|-------------------------|-------------------------|
| Wrench-Tight with Flat Guard | Part # 970309(F) | Part # 970609(F) |
| Wrench-Tight with Flat Guard | Part # 970309(G) | Part # 970609(G) |
| Hand-Tight with Zip Guard | Part # 980309(F) | Part # 980609(F) |
| Hand-Tight with Zip Guard | Part # 980309(G) | Part # 980609(G) |
| Hand-Tight with Super Zip Guard | Part # 980309(SG) | Part # 980609(SG) |
| Hand-Tight with Super Zip Guard | Part # 980309(SF) | Part # 980609(SF) |
| Zip-Roll Frame only | Part # 244278 | |



Attaches to gun that comes with units. Includes: 45° "G" thread gun adapter, 24 in. (61 cm) extension,

Zip-Roll Pressure Roller





45° Swivel Fitting Kit

To be used between the gun and Heavy-Duty Extension for pressure rolling. ("G" to "G" thread)

Part # 239531 Kit Includes (239531, 166969, 114049)



Zip-Roll Pressure Roller Covers

High-quality, all-purpose pressure roller covers. Available in a variety of naps. Part # 7721 Smooth Surfaces -9 in x 3/8 in (23 cm x .95 cm) Part # 7722 Semi-Smooth Surfaces – 9 in x 1/2 in (23 cm x 1.27 cm) Part # 7723 Medium Surfaces – 9 in x 3/4 in (23 cm x 1.90 cm) Part # 7724 Rough Surfaces – 9 in x 1 1/4 in (23 cm x 3.18 cm)

Must be ordered in multiples of 6.



Mini Poles

- Durable stainless steel construction for rust resistance
- Hand-Tight system allows for easy attachment to gun, without tools

3400 Series

• Two or more poles can be combined for extended reach

| • | Available | in | 4 | lenaths | and | "F" | and | "G" | thread | sizes | to | fit all α | ıns |
|---|-----------|----|---|---------|-----|-----|-----|-----|--------|-------|----|------------------|-----|

• For spraying ceilings, overhangs, floors, and decks

With Uni-Tip Hand-Tight Base ("G" thread only) Part # 248233 6 in (15.2 cm) 3400 Series 12 in (30.5 cm) Part # 248234 Mini Pole 18 in (45.7 cm) Part # 248235 24 in (61.0 cm) Part # 248236 With Super-Zip Hand-Tight Base Part # 3406-SF Part # 3406-SG 6 in (15.2 cm) 12 in (30.5 cm) Part # 3412-SF Part # 3412-SG 18 in (45.7 cm) Part # 3418-SF Part # 3418-SG 24 in (61.0 cm) Part # 3424-SF Part # 3424-SG With Flat Tip Base Wrench Tight 6 in (15.2 cm) Part # 2406-F Part # 2406-G 12 in (30.5 cm) Part # 2412-F Part # 2412-G Part # 2418-F Part # 2418-G 18 in (45.7 cm) 24 in (61.0 cm) Part # 2424-F Part # 2424-G

3500 Series*(with Anglehead)

| | JOO Jeries (With | Aligicileau | 346 |
|--------------------|------------------------|-----------------------|-------------|
| With Uni-Tip Hand | -Tight Base ("G" threa | ad only) | F |
| 6 in (15.2 cm) | Part # 255258 | | |
| 12 in (30.5 cm) | Part # 255259 | 3500 Series | |
| 18 in (45.7 cm) | Part # 255260 | Mini Pole | . 1 |
| 24 in (61.0 cm) | Part # 255261 | | |
| With Super-Zip Ha | nd-Tight Base | | |
| 6 in (15.2 cm) | Part # 3506-SF | Part # 3506-SG | |
| 12 in (30.5 cm) | Part # 3512-SF | Part # 3512-SG | |
| 18 in (45.7 cm) | Part # 3518-SF | Part # 3518-SG | GEOR |
| 24 in (61.0 cm) | Part # 3524-SF | Part # 3524-SG | 946 101- |
| With Flat Tip Base | Wrench Tight | | |
| 6 in (15.2 cm) | Part # 2506-F | Part # 2506-G | 3 |
| 12 in (30.5 cm) | Part # 2512-F | Part # 2512-G | 7 |
| 18 in (45.7 cm) | Part # 2518-F | Part # 2518-G | 'n |
| 24 in (61.0 cm) | Part # 2524-F | Part # 2524-G | 179 |
| | | | |

Maxi Poles

Hand-Tight Maxi Poles accept Hand-Tight adapters and an additional Maxi Pole or Mini Pole for 12 ft maximum length.

- Includes Anglehead™ to adjust spray angle
- Available in "F" and "G" thread sizes to fit all guns

| With Uni-Tip Hand-Tight Ba | se ("G" thread only) | With Super-Zip Hand-Tig | ht Base | With Flat Tip Base | | | |
|----------------------------|----------------------|--|-----------------|-----------------------|-----------------|--|--|
| Part # 248242 | 2 ft (60.9 cm) | Part # 7402-SF, 7402-SG | 2 ft (60.9 cm) | Part # 7302-F, 7302-G | 2 ft (60.9 cm) | | |
| Part # 248243 | 3 ft (91.4 cm) | Part # 7403-SF, 7403-SG | 3 ft (91.4 cm) | Part # 7303-F, 7303-G | 3 ft (91.4 cm) | | |
| Part # 248244 | 4 ft (121.9 cm) | Part # 7404-SF, 7404-SG | 4 ft (121.9 cm) | Part # 7304-F, 7304-G | 4 ft (121.9 cm) | | |
| Part # 248245 | 6 ft (182.9 cm) | Part # 7406-SF, 7406-SG | 6 ft (182.9 cm) | Part # 7306-F, 7306-G | 6 ft (182.9 cm) | | |
| Part # 248246 | 9 ft (274.2 cm) | Part # 7409-SF , 7409-SG | 9 ft (274.2 cm) | Part # 7309-F, 7309-G | 9 ft (274.2 cm) | | |

Part # **3430-G**, **3430-F** Connect two poles Part # 233951 Pole Gasket (1)

AngleHead

- In-line AngleHead Swivel provides accurate spraying at any height or angle
- Swivels to 90° (shown) for easy spraying of challenging areas
- Tip not included

| Part # 7506A | ("F" thread) no base included |
|-----------------------|--|
| Part # 7506AG | ("G" thread) no base included |
| Part # 248247 | with Uni-Tip Hand-Tight Base ("G" thread only) |
| Part # 7506-SF | with Super-Zip Hand-Tight Base |
| Part # 7506-SG | with Super-Zip Hand-Tight Base |
| Part # 7551-G | Pole Gun Adapter, Hand-Tight |
| Part # 7551-F | Pole Gun Adapter, Hand-Tight |
| Part # 87500G | With Flat Tip Guard, Wrench-Tight |
| Part # 87500F | With Flat Tip Guard, Wrench-Tight |
| Part # 7556-G | Pole Gun Adapter, Wrench-Tight |
| Part # 7556-F | Pole Gun Adapter, Wrench-Tight |
| | |



0° to 90° (90° Shown)

Gun Filters – 2-Pack

• Stainless steel mesh to eliminate rust

200 Series

Part # **248677** 60 Mesh & 100 Mesh (1 ea.)

300, 400, 500 Series and Combo Gun

| Part # 4435-2 | Extra Fine 200 Mesh | Red for varnishes and lacquers |
|----------------------|---------------------|--------------------------------|
| Part # 4434-2 | Fine 100 Mesh | Yellow for enamels and stains |
| Part # 4433-2 | Medium 50 Mesh | White for latex paints |
| Part # 4436-2 | Coarse 30 Mesh | Green for heavy-bodied paints |



Gun Repair Kits

• Includes Ball Valve Plunger Assembly and Diffuser

Part # 288817 500 Gun repair kit
Part # 4427-F, 4427-G 400 Series gun
Part # 3027-F, 3027-G 300 Series gun
Part # 6727-F, 6727-G Combo gun

Note: 400 Series Gun Repair Kits may be used in 300 Series Guns.

Pump Repair Kits

| Part # 245078 | Zip-Spray ESP |
|----------------------|---------------------|
| Part # 245569 | Zip-Spray 1700 |
| Part # 244194 | Zip-Spray 2100 Plus |
| Part # 244194 | Zip-Spray 2300 Plus |

Part # 248212 Zip-Spray 2700, 3100, 3400G, 3600G

"F" to "G" Adapter

 Converts 11/16 in (17 mm) "F" Thread to 7/8 in (22 mm) "G" Thread Part # 248248

Strainer Bags

Part # 238769 Strainer Bags available in multiples of 25







Reversible Tip Systems

From state-of-the-art features to our color-coded tip handles, we make spray tips easier to use and select. Plus, we provide the technology to give you durable, reliable equipment that delivers a consistent spray pattern for a variety of materials.

- Patented diffuser allows atomization at lower pressures, reducing tip wear and extending tip life
- Pinned handle resists twisting and breakage
- Reversible for easy cleaning
- Liquid-honed for long life and double-tested to ensure accurate spray pattern and flow rate
- Highest-quality carbide tip produces longer useable life
- Color-coded handles for easy identification

ASM's color-coded tip handle and corresponding tip selection guide make it simple to select the right orifice and fan pattern for your painting application. Follow the steps below for easy tip selection.

Spray Tip Application Guide

- 1 Identify the surface you will be spraying
- **2** Choose your coating
- **3** Determine your spray pattern width [spraying 12 in (30.5 cm) from the surface]
- 4 Follow chart to tip number

Tip handles are color-coded by orifice (tip hole) size for easy identification on the job site.


Red — 200 Mesh, For Varnishes and Lacquers

Yellow — 100 Mesh, For Enamels and Stains

White — 50 Mesh, For Latex

Green — 30 Mesh, For Heavy-Bonded Paints

How to Determine Spray Tip Size:



| | | Fan Width in | Grey | Red | Orange | Yellow | Blue | Green | Purple | Brown | Black | Filter Mesh Color |
|------------------------------------|--------------------------------|--------------------|------|------|------------|------------|------------|------------|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------------------|
| Surface | Coating | Inches | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .035 | .045 | .061 | Code |
| Wood Interiors, | | 2 in | | | | | | | | | | | | | | | | |
| vood interiors, | | _ 4 in | 209 | 211 | | | | | | | | | | | | | | |
| | Lacquer, Varnish, | 6 in | 309 | 311 | | | | | | | | | | | | | | |
| | Shellac | 8 in | 409 | 411 | 413 | | | | | | | | | | | | | |
| | | 10 in | 509 | 511 | 513 | | | | | | | | | | | | | |
| | | 12 in | 609 | 211 | 613 213 | | | | | | | | | | | | | |
| | Alkyd Stain, Alkyd Enamel, | 4 in 6 in | | 311 | 313 | | | | | | | | | | | | | |
| | Sanding Sealer | 8 in | | 411 | 413 | 415 | | | | | | | | | | | | |
| | | 2 in | | 411 | 113 | 115 | | | | | | | | | | | | |
| nterior Walls, eilings, Drywall | | 4 in | | 211 | 213 | 215 | | | | | | | | | | | | |
| elliligs, Drywali | | 6 in | | | 313 | 315 | | | | | | | | | | | | |
| | Latex, Vinyl, Acrylic | 8 in | | | | 415 | 417 | 419 | | | | | | | | | | |
| | | | | | | 515 | 517 | 519 | | | | | | | | | | |
| | | 12 in | | | | 615 | 617 | 619 | 621 | 623 | | | | | | | | |
| toof | | _ 2 in | | | 113 | 115 | | | | | | | | | | | | |
|)verhangs | | 4 in | | | 213 | 215 | 217 | | | | | | | | | | | |
| | Primer, Enamel, Latex, Acrylic | 6 in | | | | 315 | 317 | 319 | | | | | | | | | | |
| | Timer, Enamer, Eutex, Acryn | 8 IN | | | | 415 | 417 | 419 | | | | | | | | | | |
| | | 10 in | | | | 515 | 517 | 519 | | | | | | | | | | |
| | | 12 in | | | | 615 | 617 | 619 | | | | | | | | | | |
| Masonry, Block, | | 6 in | | | | 44.5 | 447 | 410 | 424 | 422 | | | | | | | | |
| tucco, Concrete | Vinyl, Oil Base, Alkyd | 8 in 10 in | | | | 415 515 | 417 517 | 419 519 | 421 521 | 423 523 | | | | | | | | - |
| | rinji, on base, rinja | 12 in | | | | 313 | 317 | 319 | 621 | 623 | | | | | | | | |
| | | 16 in | | | | 615 | 617 | 619 | 021 | 023 | | | | | | | | |
| | | 8 in | | | | 013 | 417 | 419 | 421 | 423 | | | | | | | | |
| | Latex, Acrylic | 10 in | | | | | 517 | 519 | 521 | 523 | | | | | | | | |
| | | 12 in | | | | | 617 | 619 | 621 | 623 | | | | | | | | |
| | | 6 in | | | | | | | | | | 327 | | | | | | |
| | | 8 in | | | | | | 419 | 421 | 423 | 425 | 427 | 429 | 431 | 435 | | | |
| | Smooth Elastomeric | 10 in | | | | | | 519 | 521 | 523 | 525 | 527 | | 531 | 535 | | | |
| | | _12 in | | | | | | 619 | 621 | 623 | 625 | | | 631 | 635 | 645 | 661 | |
| | | 16 in | | | | | | | | | | | | | 835 | | | |
| Vood Exteriors, | | 6 in | | | | 315 | | | | | | | | | | | | |
| hingle Siding, | Exterior | 8 in | | | | 415 | 417 | | | | | | | | | | | |
| hiplap | Stain | _10 in | | | | 515 | 517 | 519 | | | | | | | | | | |
| | | 12 in | | | | 245 | 617 | 617 | | | | | | | | | | - |
| | Vinyl, | 6 in | | | | 315 | 447 | 410 | 424 | | | | | | | | | - |
| | Acrylic, | 8 in 10 in | | | | 415 | 417 517 | 419 519 | 421 521 | | | | | | | | | H |
| | Latéx | 12 in | | | | | 617 | 619 | 621 | | | | | | | | | = |
| pen Joists | a art and its | 6 in | | | | 315 | 317 | 319 | 321 | | | | | | | | | |
| eiling Areas | Mil White | 8 in | | | | 313 | 417 | 419 | 421 | | | | | | | | | = |
| IB Deck Ceilings | High Build | 10 in | | | | | 517 | 519 | 521 | | | | | | | | | |
| .b beek cennings | High Build | 12 in | | | | | | 619 | 621 | 1 | | | | | | | | |
| | | 6 in | | | | 315 | 317 | | | | | | | | | | | |
| | Dry Fall | 8 in | | | | 415 | 417 | 419 | 421 | 423 | 425 | | | | | | | |
| | , | 10 in | | | | | 517 | 519 | 521 | 523 | 525 | | | | | | | |
| | | | | | | | | | 621 | 623 | 625 | | | | | | | |

Uni-Tip

Universal Reversible Spray Tips

- The Uni-Tip is universal with major brands, including Titan, SprayTECH, Graco RAC® IV and RAC 5 and Airlessco. Not compatible with Graco RAC X™, ASM Super-Zip or Zip-Tip™.
- Best quality carbide tip means a superior spray pattern and a longer useable fan pattern life
- The color-coded handle makes it easy to identify the tip size on the job
- Each tip individually tested for consistent fan and orifice size
- One-piece Uni-Tip seal means fewer parts on hand
- Uni-Tip seal is compatible with the full range of paints and solvents
- Pinned Handle resists twisting and breakage
- Nib on handle for seal replacement Part # **69-XXX**



- Specifically manufactured to provide crisp, clean edges
- Available in all common striping tip sizes

Part # 69xxxST

Fine-Finish Uni-Tip

- All the features of the Uni-Tip Plus, double orifice gives greater break-up of fine-finish materials
- Provides the finest atomization and a high-quality finish
- Up to 85% transfer efficiency Part # **69-FFXXX**

Uni-Tip Hand-Tight Base/Guard (Tip not included)

- Aluminum won't rust
- Virtually eliminates paint buildup and dripping
- Easy no-tools assembly
- Quickly change from horizontal to vertical spray pattern Part # 248200 "G" thread is 7/8" (22 mm)
 Part # 249303 "F" thread is 11/16" (17 mm)

Uni-Tip Seal

• Easily installs without tools! Part # 248228 (5-pack)





Standard Uni-Tips (69-XXX)

| Fan Width | Grey | Red | Orange | Yellow | Blue | Green | Purple | Brown | Black |
|-----------|------|------|--------|--------|------|-------|--------|-------|-------|-------|-------|-------|-------|-------|-------|
| in Inches | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .035 | .045 | .061 |
| 2 in | | | 113 | 115 | | | | | | | | | | | |
| 4 in | 209 | 211 | 213 | 215 | 217 | 219 | 221 | | | | | | | | |
| 6 in | 309 | 311 | 313 | 315 | 317 | 319 | 321 | 327 | | | | | | | |
| 8 in | 409 | 411 | 413 | 415 | 417 | 419 | 421 | 423 | 425 | 427 | 429 | 431 | 435 | | |
| 10 in | 509 | 511 | 513 | 515 | 517 | 519 | 521 | 523 | 525 | 527 | | 531 | 535 | | |
| 12 in | 609 | | 613 | 615 | 617 | 619 | 621 | 623 | 625 | | | 631 | 635 | 645 | 661 |
| 16 in | | | | | | | | | | | | | 835 | | |

Striping Uni-Tips (69XXXST)

| Fan Width in Inches | Yellow .015 | Blue .017 | Green .019 | Purple .021 | Black .027 |
|------------------------|----------------|--------------|---------------|----------------|---------------|
| 4 in | 215 | 217 | | | |
| 6 in | 315 | 317 | 319 | 321 | 327 |
| 8 in | | 417 | | | |
| 10 in | | 517 | | | |
| 12 in | 615 | 617 | | | |

Fine Finish Uni-Tips (69-FFXXX)

| Fan Width in Inches | Red .011 | Orange .013 | Yellow .015 | Blue .017 | Green .019 |
|------------------------|-------------|----------------|----------------|--------------|---------------|
| 4 in | 211 | 213 | 215 | | |
| 6 in | 311 | 313 | 315 | | |
| 8 in | 411 | 413 | 415 | | |
| 10 in | | 513 | | 517 | |
| 12 in | | | | | 619 |



Super-Zip

Reversible Spray Tips

- Liquid-honed and double-tested to ensure an accurate spray pattern
- Patented diffusion chamber for superior atomization
- Color-coded tip handles for easy selection
- Reversible to quickly clear tip clogs Part # **59**-xxx

Striping Super-Zips

- Specifically manufactured to provide crisp, clean edges
- Available in all common striping tip sizes (213, 215, 315, 217, 317, 417, 219, 319, 419, 321, 421, 621, 323, 623, 625, 327, 627)
 Part # 59xxxST

Fine-Finish Super-Zips

- Double orifice gives greater break-up of fine-finish materials
- Provides the finest atomization and a high-quality finish
- Up to 85% transfer efficiency Part # **59FFXX-XXX**



| | Fine-Finish Super Zips | | | | | | | | | | | |
|----|------------------------|-----|-----|-----|-----|-----|-----|--|--|--|--|--|
| 09 | 111 | 211 | 311 | 411 | 511 | 611 | 711 | | | | | |
| 11 | 113 | 213 | 313 | 413 | 513 | 613 | 713 | | | | | |
| 13 | 115 | 215 | 315 | 415 | 515 | 615 | 715 | | | | | |
| 15 | 117 | 217 | 317 | 417 | 517 | 617 | 717 | | | | | |
| 17 | 119 | 219 | 319 | 419 | 519 | 619 | 719 | | | | | |
| 19 | 121 | 221 | 321 | 421 | 521 | 621 | _ | | | | | |

Tip size imprinted on handle Handle color-coded

denoting orifice size Locking tab

Patented diffuser chamber

Tungsten carbide spray tip

Hardened stainless steel barrel

Super-Zip Hand-Tight Base/Guard

- Hand-Tight Base no tools required!
- Patented Cartridge Seal is compatible with all materials, will last through multiple tips and is spring-loaded for easy tip insertion and removal
- Patented safety tab design locks for safe tip reversing when unclogging tip
- Available to fit all makes of guns

Part # **5901-F** Fits "F" thread size - 11/16 in (17 mm) Part # **5901-G** Fits "G" thread size - 7/8 in (22 mm)

Super-Zip Cartridge Seals

- Replace Cartridge Seals quickly, without tools
- No loose gaskets

Part # 5907 Hand-Tight Cartridge Seal


Super-Zip Selection Guide

| • | | • | | | | | | | | | | | | | | | | | | | | |
|------------------------------|-----------------------|--------|-----------------------|--------|------------------------|--------|------------------------|--------|-----------------------|--------|-----------------------|--------|------------------------|--------|-----------------------|--------|-----------------------|--------|-----------------------|--------|-----------------------|--------|
| FAN WIDTH IN INCHES | GREY .009 0.08 | FILTER | RED .011 0.12 | FILTER | Orange .013 0.17 | FILTER | YELLOW .015 0.23 | FILTER | BLUE .017 0.30 | FILTER | GREEN .019 0.36 | FILTER | PURPLE .021 0.46 | FILTER | BROWN .023 0.55 | FILTER | BLACK .025 0.66 | FILTER | BLACK .027 0.77 | FILTER | BLACK .029 0.88 | FILTER |
| 2 in | • | | 111 | | 113 | | 115 | | 117 | | 119 | | 121 | | • | | • | | • | | • | \Box |
| 4 in | 209 | | 211 | | 213 | | 215 | | 217 | | 219 | | 221 | | • | | • | | • | | • | |
| 6 in | 309 | | 311 | | 313 | | 315 | | 317 | | 319 | | 321 | | 323 | | 325 | | 327 | | • | |
| 8 in | 409 | | 411 | | 413 | | 415 | | 417 | | 419 | | 421 | | 423 | | 425 | | 427 | | 429 | |
| 10 in | • | | 511 | | 513 | | 515 | | 517 | | 519 | | 521 | | 523 | | 525 | | 527 | | 529 | |
| 12 in | • | | 611 | | 613 | | 615 | | 617 | | 619 | | 621 | | 623 | | 625 | | 627 | | 629 | |
| 14 in | • | | • | | • | | 715 | | 717 | | 719 | | 721 | | 723 | | 725 | | • | | 729 | |
| 16 in | • | | • | | 813 | | 815 | | 817 | | 819 | | 821 | | 823 | | • | | 827 | | 829 | |
| 18 in | • | | • | | • | | 915 | | 917 | | • | | 921 | | • | | 925 | | • | | • | \Box |
| FAN WIDTH IN INCHES | BLACK .031 1.02 | FILTER | BLACK .033 1.16 | FILTER | BLACK .035 1.31 | FILTER | BLACK .039 1.62 | FILTER | BLACK .041 1.79 | FILTER | BLACK .043 1.98 | FILTER | BLACK .045 2.16 | FILTER | BLACK .047 2.36 | FILTER | BLACK .049 2.57 | FILTER | BLACK .051 2.81 | FILTER | BLACK .053 3.00 | FILTER |
| 2 in | • | | • | | • | | • | | • | | • | | • | | • | | • | | • | | • | |
| 4 in | | | • | | • | | • | | • | | • | | • | | • | | • | | • | | • | |
| 6 in | 331 | | 333 | | 335 | | 339 | | • | | • | | • | | • | | • | | • | | • | |
| | 431 | ı | 422 | | 40.5 | | | | | | | | | | | | | | | | | |
| 8 in | | | 433 | | 435 | | 439 | | 441 | | 443 | | 445 | | 447 | | 449 | | 451 | | 453 | |
| 8 in 10 in | 531 | | 533 | | 535 | | 439 539 | | 441 541 | | 443 543 | | 445 545 | | 447 547 | | 449 549 | | 451 551 | | 453 553 | |
| _ | 531 631 | | 533 633 | | 535 635 | | 539 639 | | 541 641 | | 543 643 | | 545 645 | | | | | | 551 651 | | 553 653 | |
| 10 in | 531 | | 533 | | 535 | | 539 | | 541 | | 543 | | 545 | | 547 | | 549 | | 551 | | 553 | |
| 10 in 12 in | 531 631 | | 533 633 | | 535 635 | | 539 639 | | 541 641 | | 543 643 | | 545 645 | | 547 647 | | 549 649 | | 551 651 | | 553 653 | |



REFERENCE

----- COLOR ----- ORIFICE SIZE ----- GPM / FLOW



Flat Tip Systems

Standard Flat Tips

• Flat Tips are universal and fit all makes of Flat Tip Bases Part # 90-xxx

Flat Tip Base/Guard

- Flat Tip Bases are universal and are available to fit all makes of guns
- Accommodates Flat Tip-n-Gasket (93-xxx) and Standard Flat Tips (90-xxx) Fits "F" thread size - 11/16 in (17 mm) Fits "G" thread size - 7/8 in (22 mm) Part # 420-G
- Separate tip gasket available in tubes of eight (8)







Flat Tip Selection Guide

| | | | | | | | | | | | | | | | | | | | | REFERENCE |
|---|-----------------------------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|----------------------------|
| | Fan Width In Nches | .007 0.04 | FILTER | .009 0.08 | FILTER | .011 0.12 | FILTER | .013 0.17 | FILTER | .015 0.23 | FILTER | .017 0.30 | FILTER | .019 0.36 | FILTER | .021 0.46 | FILTER | .023 0.55 | FILTER | ORIFICE SIZE GPM / FLOW |
| | 2 in | • | | 109 | | 111 | | 113 | | 115 | | • | | 119 | | 121 | | • | | |
| Г | 4 in | 207 | П | 209 | | 211 | | 213 | | 215 | П | 217 | | 219 | П | 221 | | 223 | П | |
| Г | 6 in | 307 | П | 309 | | 311 | | 313 | | 315 | | 317 | | 319 | П | 321 | П | 323 | П | |
| Г | 8 in | 407 | П | 409 | | 411 | | 413 | | 415 | | 417 | | 419 | П | 421 | П | 423 | П | |
| Г | 10 in | • | П | 509 | | 511 | | 513 | | 515 | | 517 | | 519 | П | 521 | П | 523 | П | |
| Г | 12 in | • | П | 609 | | 611 | | 613 | | 615 | | 617 | | 619 | П | 621 | П | 623 | П | |
| Г | 14 in | • | П | • | | • | | • | | 715 | | 717 | | 719 | | 721 | П | 723 | П | |
| Г | 16 in | • | Π | • | | • | | 813 | | 815 | | 817 | | 819 | | 821 | | 823 | Π | |
| Г | 18 in | • | | • | | • | | • | | • | | 917 | | • | | 921 | | • | П | |

| FAN WIDTH IN INCHES | .025 0.66 | FILTER | .027 0.77 | FILTER | .029 0.88 | FILTER | .031 1.02 | FILTER | .033 1.16 | FILTER | .035 1.31 | FILTER | .039 1.62 | FILTER | .043 1.98 | FILTER | .045 2.16 | FILTER | .051 2.81 | FILTER | .055 3.17 | FILTER |
|------------------------------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|--------------|--------|
| 2 in | • | | • | | • | | • | | • | | • | | • | | • | | • | | • | | • | |
| 4 in | • | | 227 | | • | | • | | • | | 235 | | • | | • | | • | | • | | • | |
| 6 in | 325 | | 327 | | • | | 331 | | • | | • | | • | | • | | • | | • | | • | |
| 8 in | 425 | | 427 | | 429 | | 431 | | 433 | | 435 | | 439 | | • | | • | | 451 | | • | |
| 10 in | 525 | П | 527 | | 529 | | 531 | П | 533 | П | 535 | | • | | 543 | | • | | • | | • | |
| 12 in | 625 | | 627 | | 629 | | 631 | | 633 | | 635 | | • | | • | | 645 | | • | | 655 | |
| 14 in | 725 | | • | | 729 | | • | | • | | 735 | | • | | • | | • | | • | | • | |
| 16 in | • | | 827 | | 829 | | 831 | | 833 | | 835 | | • | | • | | • | | • | | • | |
| 18 in | 925 | Г | • | | • | Г | • | | • | | 935 | | • | | • | | • | | • | | • | |





Texture Application Guide

Get the Interior and Exterior Texture Finish You Want

Interior Texture

Simulated Acoustic (Popcorn)



Orange Peel, Fine Splatter



Splatter



Knockdown



Smooth, Level 5 and Skim Coat

Commonly Used Materials

- Ceiling Spray Textures Containing Polystyrene or Vermiculite Aggregate (Fine, Medium, Coarse)
- All-Purpose Joint Compounds
- Lightweight Joint Compounds
- Wall and Ceiling Spray Textures
- All-Purpose Joint Compounds
- Lightweight Joint Compounds
- Wall and Ceiling Spray Textures
- All-Purpose Joint Compounds
- Lightweight Joint Compounds
- Wall and Ceiling Spray Textures
- All-Purpose Joint Compounds
- Lightweight Joint Compounds
- Wall and Ceiling Spray Textures
- Skim Coat Materials
- Wall Surfacing Materials

Exterior Texture Not suitable for stucco or EIFS materials

Textured Acrylics and **Elastomerics**



Deck Coatings



Commonly Used Materials

- Textured Acrylic Materials
- Textured Elastomeric Materials
- Decorative and Anti-Skid Deck Coatings

Zip-Tex Spray Nozzles Part # 234153

Black 12 mm Acoustics Large Knockdown Popcorn Beige 4 mm Fine Finish Orange Peel White 6 mm Orange Peel Fine Spatter Gray 8 mm Splatter Small to Med Knockdown

Texture Sprayers

ASM Zip-Tex texture units are manufactured by the worlds leading manufacturer of airless spray equipment. Our pumping systems are built rugged and are designed for large and small jobs offering a less fatiguing and better way to add texture coatings. ASM offers two texture spray systems for the contractor who is ready to graduate from the traditional hopper gun. ASM's texture units deliver a smooth material flow for uniform coverage and a consistent and professional pattern.

Interior Coatings:

Exterior Coatings:

Popcorn Orange Peel Textured Acrylics and Elastomerics Deck Coatings

Splatter

Not suitable for Stucco or EIFS coatings

. Knockdown

Smooth Level 5 or Skim Coat

Zip-Tex 650

Interior Texture Sprayer

The Zip-Tex 650 is the perfect pumping system for tradesmen and contractors who are ready to graduate from a hopper gun to a faster, more productive, less-fatiguing spray rig. Just add air.

Innovative Pump-Only Texture Sprayer

- Small, lightweight and portable easy to bring on and off the job site
- weight: 25 lbs (11.3 kg)

RotoFlex II[™] **Texture Pump**

- Delivers smooth material flow for uniform coverage and a consistent pattern
- Provides material flow rates up to .65 gpm for faster applications

Superior Texture Projection

 Pumping system force-feeds material through the texture gun and projects texture farther than a traditional hopper gun

Material Hopper

 Holds 5 gallons of material, allowing you to complete a whole room without stopping to refill

Includes

Unit, Gun, 6 mm and 8 mm nozzles, 20 ft material hose and viscosity ball



Part # 254982 UPC # 69946089943



IMPORTANT:

 Designed for use with a user-supplied air compressor minimum air compressor rating 3.5 cfm at 40 psi; .09 m²/min

Zip-Tex 900

Interior Texture Sprayer

The all new Zip-Tex 900 is the perfect choice for the contractor who's looking to spray high-quality texture finishes with a simple-to-use, self-contained machine.

New RotoFlex II Texture Pump

- Features an innovative braided sling that provides extra support to the RotoFlex pump tube for higher performance and life
- Delivers smooth material flow for uniform coverage and a consistent spray pattern

New Higher-Production Performance Points

- Max output .9 gallons per minute (Finish jobs even faster)
- Material flow increased by more than 20% over the previous model 750.
- Material pressure max 60 psi, 4.2 bar boosted by more than 10% over the 750 handle thicker mud mixes

New Higher-Capacity On-Board Air Compressor

- Compressor Air Output: 8.7 displacement cfm; 4.0 cfm at 45 psi; 4.0 m³/min
- 20% greater air output than the 750. Projects material further
- Complete air-consuming splatter and orange peel finishes jobs faster

New Larger-Capacity Hopper

- Holds 8 gallons of material for more time spraying between refills
- Ultra-low entry height of 32 inches makes filling the hopper easier

Exclusive Dual-Use Gun

- Versatile, patent-pending design converts quickly to a hopper gun for touch-up jobs
- Easy-to-use air trigger adjustments on the gun
- New through-handle air passage prevents material from contaminating the needle spring

New Single-Motor Design

- One motor operates the pump and air compressor, making the sprayer smaller and 15 lbs (7 kg) lighter
- Delivers 1.7 hp for optimal performance

Touch-Up Hopper (included)

- Attaches to air spray gun without tools for completing quick jobs and touch-ups
- 3/4-gallon capacity

Includes

Unit, Gun, 25 ft material and air hose, touch-up hopper, 4 nozzles and viscosity ball $\,$



Part # 254983 UPC # 769946089950

ASM Professional Hopper Gun

Sprays acoustics, drywall mud, waterproofing material, pool deck sealant, stucco, and most gravity-fed materials. Angled 1-1/2 gallon (5.7 L) hopper allows more material capacity for longer spraying before refills!

Zip-Tex 650 Gun

Part # 288906 Gun only

Zip-Tex 750, 900 and 1000

Part # 288905 Gun only

Part # 246409 Gun including Hopper

Spray Nozzles & Replacement Parts

Part # 234153 Spray Nozzles

Beige, 4 mm — Fine Finish, Orange Peel White, 6 mm — Orange Peel, Fine Splatter

Gray, 8 mm — Splatter, Small to Medium Knockdown Black, 12 mm — Acoustics, Large Knockdown, Popcorn

Part # 234149 25 ft (7.6 m) Material/Air Hose (Zip-Tex 750, 900 & 1000)

Part # 288622 20 ft Material/Air Hose Kit for Zip-Tex 650

Part # 15C090 Viscosity Ball – All Machines

Part # 234156 RotoFlex Replacement Pump Hose (Zip-Tex 750 & 1000 only)

Recommended replacement after 2000-2500 gallons (7571-9463 L) of gypsum-based material

Part # 288623 RotoFlex II Replacement Pump Hose (Zip-Tex 650 & 900 only)

Part # 234159 Gun Repair Kit (All guns except 288906 Gun)

Part # 258000 Gun Repair Kit for 288906 Gun

Part # 234162 Material Hose Plug and Hopper Gun Attachment Plug

Part # 234188 Hopper Clamp



Zip-Clean

Direct Drive Pressure Washers

Zip-Clean pressure washers offer innovative features to make your job easier, and reliable components to make you more productive. You'll spend less time on machine set-up with our one-hand hose connection and built-in chemical injector. Use Zip-Clean pressure washers for surface preparation before painting houses, decks, fences, buildings and more.

- Dependable Honda® overhead valve engines
- General pump with unloader, thermal relief, and over-pressure protection
- Low-profile cart for easy transport; easy to lift
- Double swivel on high pressure hose prevents tangling
- Self-siphoning chemical hose
- Features a steel powder-coated cart, built-in chemical injector, nozzle holder, and gun-hose rack

Zip-Clean 2525

Perfect for those who need a washer heavy-duty enough to get the job done, without the investment of a commercial-grade model.

- 2500 psi (172 bar) at 2.5 gpm (9.5 lpm)
- 160cc Honda GC series motor
- Radial axial pump with thermal protection
- 30 ft (9.1 m) hose (Maximum)
- Includes chemical injector and set of 3 nozzles 0°, 15° and 40°
- 1 year limited warranty





Zip-Clean 2525

2500 psi (17.2 MPa, 172 bar) 160cc Honda GC series motor Part # 246602 UPC # 769946080407

Includes:

- 30 ft (9.1 m) high pressure hose
- Heavy-duty gun and wand
- 4 color-coded quick-connect spray nozzles (3 spray nozzles, 1 chemical injection nozzle)

Zip-Clean 2730

2700 psi (18.6 MPa, 186 bar) @ 2.4 gpm (9 lpm) 200cc Honda OHV Engine Part # 245348 UPC # 769946075663

Includes:

- 50 ft (15.2 m) high pressure non-marking hose
- Heavy-duty gun and wand
- 4 color-coded quick-connect spray nozzles (3 spray nozzles, 1 chemical injection nozzle)



Zip-Clean 3030

3000 psi (20.6 MPa, 206 bar) @ 3.0 gpm (11 lpm) 270cc Honda OHV Engine Part # 245349 UPC # 769946075670

Includes:

- 50 ft (15.2 m) high pressure non-marking hose
- Heavy-duty gun and wand
- 4 color-coded quick-connect spray nozzles
 (3 spray nozzles, 1 chemical injection nozzle)



Standard Nozzles (2525)(2730)

Part # **244768** - Includes: 0°, 15°, 25°, 40°

Part # 805634 - Includes:

Chemical Injector Nozzle

Part # 805535 - 0° Red

Part # 805536 - 15° Yellow

Part # **805537** - 25° Green

Part # 805538 - 40° White

Standard Nozzle (3030)

Part # **244769** - Includes: 0°, 15°, 25°, 40°

Part # 805634 - Includes:

Chemical Injector Nozzle

Part # **805539** - 0° Red

Part # 805540 - 15° Yellow

Part # **805541** - 25° Green

Part # 805542 - 40° White

Rotating Nozzle

Part # 198012

Oscillating Nozzle (Not Shown)

Part # 198013



High Pressure Non-Marking Hose

3/8 in x 50 ft (10 mm x 15 m), 3000 psi (21.0 MPa, 210 bar) Part # **245416 for 2730/3030**

3/8 in x 30 ft (10 mm x 8 m), 3000 psi (21.0 MPa, 210 bar) Part # **118125** for **2525**



Guns

Part # 244784

Gun with vented composite wand handle and quick-connect fittings, 5000 psi (344 bar, 34.4 MPa) max. working pressure

Part # 246674 for use with 2525 only Gun only

Part # 118124 Gun Extension for 2525



Fluids

ASM fluids and protectants keep your equipment in top performing condition. ASM fluids are approved for use in all airless pumps.

Pump Life

- Protects pump from corrosion and rust during shortand long-term storage
- Lubricates and cleans to help stop sticking valve seats
- Freeze proof to -30° F (-34° C)
 Part # 245650 (8 oz, 237 ml; 48 per case)
 245423 (32 oz, 946 ml; Available in multiples of 6)

Packing Seal

- Prevents coating material from adhering to the pump's piston rod
- Prolongs pump packing life in all brands of piston pumps Part # 245427 (8 oz, 237 ml; Available in multiples of 6)
 Part # 245428 (32 oz, 946 ml; Available in multiples of 12)

Hydraulic Fluid

- Non-foaming formula
- Resists emulsifying and chemical breakdown Part # **245425** (32 oz, 946 ml; Available in multiples of 12)

Starter Kit

• For lubrication and protection
Part # **245651** (8 oz, 237 ml; Pump Life) (4 oz, 119 ml; Packing Seal)



Visit your local Dealer for ASM Accessories located in these merchandise racks.

Revolving Locking Tower Floor Merchandiser



Requires 4 Square feet 24 in Wide x 24 in Deep x 91 in High.

Wall or Counter Locking Merchandiser



13 in Wide x 7 in Deep x 26 in or 30 in High without header.

For more information contact ASM Customer Service at 1-800-854-4025

AIRLESS PRODUCT SPECIFICATIONS



| Model | Zip-Spray ESP | Zip-Spray 1700 | Zip-Spray 2100 Plus | Zip-Spray 2300 Plus | Zip-Spray 2700 Plus | Zip-Spray 3100 Plus |
|--------------------------|---|---|--|--|--|--|
| Part Number: | 248772 (120V) 248850 (240V)* | 233789 (120V) | 247485 (Cart) 247482 (Stand) 247484 (240V Stand)* 247487 (240V Cart)* | 247531 247533 (240V)* | 247558 247565 (240V)* | 247559 |
| Max Tip: | .015 | .017 | .021 | .023 | .027 | .031 |
| Max psi/bar: | 2800 psi (19.3 MPa, 19.3 bar) | 3000 psi (20.7 MPa, 207 bar) | 3300/227 | 3300/227 | 3300/227 | 3300/227 |
| Max gpm/lpm: | .24 gpm (.91 lpm) | .31 gpm (1.17 lpm) | .47/1.8 | .54/2.0 | .86/3.3 | 1.1/4.2 |
| Weight lbs/kg: | 21 lbs | 36 lbs | 36 lbs Stand, 65 lbs Cart | 66 lbs Cart | 100 lbs | 104 lbs |
| Max Hose Length: | 75 ft (45.7/91.4 m) depending on tip size | 150 ft (45.7/91.4 m) depending on tip size | 150/300 ft (45.7/91.4 m) depending on tip size | 150/300 ft (45.7/91.4 m) depending on tip size | 150/300 ft (45.7/91.4 m) depending on tip size | 150/300 ft (45.7/91.4 m) depending on tip size |
| Motor: | 3/8 HP | 3/4 HP | 5/8 HP DC | 7/8 HP | 1.75 HP Brushless | 2.0 HP Brushless |
| Generator Requirements: | | | 3000W | 3000W | 5000W | 5000W |
| Gun Support: | | | | | 1 Gun .027 Tip 2 Guns .017 Tip | 1 Gun .031 Tip 2 Guns .019 Tip |
| Sprayer Includes: | 200 Contractor Spray Gun with 4-finger trigger 515 Uni-Tip with Hand-Tight Base Hose: 1/4 in x 25 ft (6.3mm x 7.6m), 3300 psi (22.7 MPa, 227 bar) airless paint hose Pump Life Protectant Fluid | 500 Series Professional Airless Spray Gun with 2-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4 in x 50 ft (6.3mm x 15.2m), 3300 psi (22.7 MPa, 227 bar) airless paint hose Pump Life Protectant Fluid | 500 Series Professional Airless Spray Gun with 2-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4" x 50' (6.4mm x 15m) 3300 psi (227 bar) Pump Life Protectant Fluid | 500 Series Professional Airless Spray Gun with 2-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4" x 50' (6.4mm x 15m) 3300 psi (227 bar) Pump Life Protectant Fluid | 500 Series Professional Airless Spray Gun with 2-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4" x 50' (6.4mm x 15m) 3300 psi (227 bar) Pump Life Protectant Fluid | 500 Series Professional Airless Spray Gun with 2-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4" x 50' (6.4mm x 15m) 3300 psi (227 bar) Pump Life Protectant Fluid |
| Pump Filter: | | | Includes Easy Out Pump Filter |
| Easy Out Filter Screens: | | | • 60 Mesh - 245527 • 100 Mesh - 245528 • 200 Mesh - 245526 | • 60 Mesh - 245527 • 100 Mesh - 245528 • 200 Mesh - 245526 | 30 Mesh- 244071 60 Mesh- 244067 100 Mesh- 244068 200 Mesh- 244069 | • 30 Mesh- 244071 • 60 Mesh- 244067 • 100 Mesh- 244068 • 200 Mesh- 244069 |
| Dimensions: | • 14.9 L x 15.0 W x 15.6 H (in) 37.8 L x 38.1 W x 39.6 H (cm) | • 19.5 L x 17.25 W x 40.75 H (in) 49.5 L x 43.8 W x 103.5 H (cm) | • Cart - 22.0 L x 20.5 W x 38.8 H (in) 55.9 L x 52.1 W x 98.6 H (cm) • Stand - 15.75 L x 14.0 W x 17.0 H (in) 40.0 L x 36.0 W x 43.0 H (cm) | • Cart - 22.0 L x 20.5 W x 38.8 H (in) 55.9 L x 52.1 W x 98.6 H (cm) | • Cart - 26.5 L x 22.5 W x 38.75 H (in) 67.3 L x 57.2 W x 98.4 H (cm) | • Cart - 26.5 L x 22.5 W x 38.75 H (in) 67.3 L x 57.2 W x 98.4 H (cm) |
| Repair Parts: | Inlet Strainer - 245578 Pump Repair Kit - 245078 | • Pump Repair Kit: 245569 | • Inlet Strainer - 276897 • Packing Kit - 244194 • Rod - 249125 • Cylinder - 243176 Complete Pump Lower: • Part # 255475 | • Inlet Strainer - 276897 • Packing Kit - 244194 • Rod - 249125 • Cylinder - 243176 Complete Pump Lower: • Part # 255475 | • Inlet Strainer - 189920 • Packing Kit - 248212 • Rod- 248206 • Sleeve- 248209 Complete Pump Lower: • Part # 248204 | Inlet Strainer - 189920 Packing Kit - 248212 Rod- 248206 Sleeve - 248209 Complete Pump Lower: Part # 248204 |
| Manuals: | | | • Operation - 312360 • Repair - 312361 • Pump - 312362 • Gun - 312363 | Operation - 312360Repair - 312361Pump - 312362Gun - 312363 | Operation- 312538Repair- 312537Pump- 310643Gun- 312363 | Operation- 312538 Repair- 312537 Pump- 310643 Gun- 312363 |
| Warranty: | year warranty against defects, materials and workmanship; excluding wear parts. | 1 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. |

^{* 240}V Units are not sold domestically









| Zip-Spray 3600 G Plus |
|---|
| 247560 |
| 025 |
| .036 |
| 3300/227 |
| 1.25/4.7 |
| 113 lbs 150/300 ft (45.7/91.4 m) depending on tip size |
| |
| |
| (1) Gun with .036 (2) Guns with .023 (3) Guns with .018 |
| 500 Series Professional Airless Spray Gun with Z-finger trigger 517 Uni-Tip with Uni-Tip Hand-Tight Base Hose: 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (227 bar) Pump Life Protectant Fluid |
| Includes Easy-Out Pump Filter |
| • 30 Mesh - 246425 • 60 Mesh - 246384 • 100 Mesh - 246382 • 200 Mesh - 246383 |
| • Cart - 32 L x 22.25 W x 31.5 H (in) 81 L x 56.5 W x 80 H (cm) |
| Inlet Strainer - 189920 Packing Kit - 248212 Chromex Rod - 248206 Cylinder - 287551 Sleeve - 248209 Piston Valve - 239937 Intake Valve Kit - 246429 30/55 Gallon Siphon Kit - 287541 Complete Pump Lower: Part # 287512 |
| 1 242576 |

• Instruction - 312576 • Repair - 312586

2 year warranty against defects, materials and workmanship; excluding wear parts.

| Model | Zip-Tex 650 | Zip-Tex 900 |
|---------------------------|---|---|
| Part Number: | 254982 | 254983 |
| Max psi/bar: | 50/3.5 | 60/4.2 |
| Max gpm/lpm: | .65/2.5 | .9/2.5 |
| Weight lbs/kg: | 25/11.3 | 60/27.2 |
| Max Hose Length: | 20 ft (6 m) | 25 ft (6 m) |
| Motor: | 1.0 HP | 1.7 HP |
| Compressor Air Output: | User supplied air compressor required Minimum air compressor rating 3.5 cfm @ 40 psi (.09 m/min) | 8.7 Displacement cfm - (sm.ltrs) 4.0 cfm @ 45 psi (.1 m/min) |
| Sprayer Includes: | Hopper: 5 gal Contractor Texture Gun Tips/Discs Supplied with Trigger Gun: 6 mm, 8 mm 20 ft material hose | Hopper: 8 gal Contractor Texture Gun Tips/Discs Supplied with Trigger Gun: 4 mm, 6 mm, 8 mm, 12mm 3/4 gal Touch-up Hopper 25 ft Material/Air hose |
| Dimensions: | • 12 W x 20 L x 20 H (in) • 30 W x 51 L x 51 H (cm) | • 18 W x 23 L x 41 H (in) • 46 W x 58 L x 100 H (cm) |
| Repair Parts: | • Gun - 288906 • 20 ft Air/Material Hose - 288622 • RotoFlex II Hose - 288623 | • Gun - 288905 • Gun/Hopper - 246409 • 25 ft Material/Air Hose - 234149 • RotoFlex II Hose - 288623 |
| Manuals: | • Operation - 311766 • Repair - 311774 | • Operation - 311766 • Repair - 311774 |
| Materials Sprayed | Simulated acoustic and drywall mud | Simulated acoustic and drywall mud |
| Typical Applications | Residential and light commercial interiors | Residential and light commercial interiors |
| Warranty: | 1 year warranty against defects, materials and workmanship; excluding wear parts. | 1 year warranty against defects, materials and workmanship; excluding wear parts. |
| | | , |

| Model | Zip-Clean 2525 Direct-Drive | Zip-Clean 2730 Direct-Drive | Zip-Clean 3030 Direct-Drive |
|-----------------------|--|---|--|
| Part Number: | 246602 | 245348 | 245349 |
| Operating Pressure: | 2500 psi (172 bar, 17.2 MPa) | 2700 psi (186 bar, 18.6 MPa) | 3000 psi (206 bar, 20.6 MPa) |
| Water Pump Flow Rate: | 2.5 gpm (9.5 lpm) | 2.7 gpm (10.2 lpm) | 3.0 gpm (11 lpm) |
| Weight lbs/kg: | 70 lb (32 kg) | 99 lb (45 kg) | 135 lb (61 kg) |
| Fuel Tank Capacity: | 1.8 qt (1.8 liter) | 3.8 qt (3.6 liter) | 6.2 qt (6.1 liter) |
| Motor: | (4 cycle, air-cooled): 160cc Honda GC Series | (4 cycle, air-cooled): 200cc Honda OHV | (4 cycle, air-cooled): 270cc Honda OHV |
| Pump Type: | Radial Axial Pump | General Pump, Triplex Piston Ceramic Plunger | General Pump, Triplex Piston Ceramic Plunger |
| Tips: | 0° Red - 805535 15° Yellow - 805536 25 Green - 805537 40° White - 805538 81ack Chemical Injector - 805634 Set of 4 Tips (0°, 15°, 25°, 40°) - 244768 | 0° Red - 805535 15° Yellow - 805536 25° Green - 805537 40° White - 805538 81ack Chemical Injector - 805634 Set of 4 Tips (0°, 15°, 25°, 40°) - 244768 | 0° Red - 805539 15° Yellow - 805540 25° Green - 805541 40° White - 805542 8162 Chemical Injector 805634 Set of 4 Tips (0°, 15°, 25°, 40°) - 244769 |
| Dimensions: | Dimensions: • 22 W x 23.5 L x 34 H (in) • 56 W x 60 L x 86 H (cm) | Dimensions: • 21.5 W x 35.5 L x 34 H (in) • 55 W x 90 L x 86 H (cm) | Dimensions: • 21.5 W x 35.5 L x 34 H (in) • 55 W x 90 L x 86 H (cm) |
| Replacement Parts: | • Gun only - 246674 • Wand Extension - 118124 • Hose - 118125 | • Gun - 288905 • Gun/Hopper - 246409 • 25 ft Material/Air Hose - 234149 • RotoFlex II Hose - 288623 | • Gun & Wand -244784 • Hose - 245416 |
| Manuals: | Instruction - 309829 | Instruction - 309424 Repair - 309425 | Instruction - 309424 Repair - 309425 |
| Warranty: | 1 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. | 2 year warranty against defects, materials and workmanship; excluding wear parts. |

ASM CUSTOMER SERVICE

20500 David Koch Ave. Rogers, MN 55374 Phone: 800-854-4025

Fax: 800-228-5104

VISIT US ON THE WEB FOR PROMOTIONS, PRODUCT UPDATES, MANUALS, DEALERS, SERVICE CENTERS AND GENERAL INFORMATION

WARRANTY

ASM warrants its products to be free of defects in material and workmanship for one year (See operation manual for complete warranty information)

ASM AUTHORIZED SERVICE AGENCIES

Call 1-800-854-4025 or see our website for the nearest ASM Authorized Service Agency.

www.asmcompany.com



©2008 ASM Company. Form No. 335000 Rev. G 12/08 Printed in U.S.A. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.